



**SAFETY DATA SHEET**  
GUNK FOAM ENGINE DEGREASANT - AEROSOL

**Page:** 1  
**Compilation date:** 26/03/2015  
**Revision No:** 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** GUNK FOAM ENGINE DEGREASANT - AEROSOL  
**Product code:** 6729

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Granville Oil & Chemicals Ltd.  
Unit 29 Goldthorpe Industrial Estate  
Goldthorpe  
Rotherham  
South Yorkshire  
S63 9BL  
United Kingdom  
**Tel:** +44 (0)1709 890099  
**Fax:** +44 (0)1709 891121  
**Email:** [technical@granvilleoil.com](mailto:technical@granvilleoil.com)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0)1709 890099  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CHIP:** F+: R12; -: R52/53

**Classification under CLP:** Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; -: H229; Skin Irrit. 2: H315; Eye Irrit. 2: H319

**Most important adverse effects:** Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**2.2. Label elements**

**Label elements under CLP:**

**Hazard statements:** H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H412: Harmful to aquatic life with long lasting effects.

**Signal words:** Danger

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 2

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark



**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

**Label elements under CHIP:**

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.

S24/25: Avoid contact with skin and eyes.

S29: Do not empty into drains.

S51: Use only in well-ventilated areas.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 3

## Hazardous ingredients:

### PROPANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%

### PROPAN-2-OL

200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%
-----------	---------	-------------------------	--	-------

### BUTANE

203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	---	-------------------------------------	-------

KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), SWEETENED - REACH registered number(s): 01-2119502385-46

294-799-5	91770-15-9	Xn: R65; N: R51/53	Asp. Tox. 1: H304; Aquatic Chronic 2: H411	1-10%
-----------	------------	--------------------	---	-------

KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), HYDRODESULPHURIZED - REACH registered number(s): 01-2119462828-25

265-184-9	64742-81-0	Xn: R65; N: R51/53	Asp. Tox. 1: H304; Aquatic Chronic 2: H411	1-10%
-----------	------------	--------------------	---	-------

### ISOBUTANE

200-857-2	75-28-5	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	---	-------------------------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

[cont...]

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 4

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools. Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

[cont...]

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 5

## 8.1. Control parameters

Hazardous ingredients:

### PROPANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m <sup>3</sup>	7200 mg/m <sup>3</sup>	-	-

### PROPAN-2-OL

UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-
----	-----------------------	------------------------	---	---

### BUTANE

UK	1450 mg/m <sup>3</sup>	1810 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

### ISOBUTANE

UK	2400 mg/m <sup>3</sup>	9600 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

## DNEL/PNEC Values

Hazardous ingredients:

### KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), SWEETENED

Type	Exposure	Value	Population	Effect
DNEL	Oral	19mg/kg/24h	Consumers	Systemic

### KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), HYDRODESULPHURIZED

Type	Exposure	Value	Population	Effect
DNEL	Oral	19mg/kg/24h	Consumers	Systemic

## 8.2. Exposure controls

**Engineering measures:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Chemically resistant gloves

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Aerosol

**Colour:** White

**Odour:** Pleasant

**Flash point°C:** -60

[cont...]

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 6

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

**Toxicity values:** No data available.

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

[cont...]

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 7

## 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

## 12.4. Mobility in soil

**Mobility:** No data available.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Disposal of packaging:** Not applicable.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1950

### 14.2. UN proper shipping name

**Shipping name:** AEROSOLS

### 14.3. Transport hazard class(es)

**Transport class:** 2

### 14.4. Packing group

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D

**Transport category:** 2

[cont...]

# SAFETY DATA SHEET

GUNK FOAM ENGINE DEGREASANT - AEROSOL

Page: 8

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H220: Extremely flammable gas.  
H222: Extremely flammable aerosol.  
H225: Highly flammable liquid and vapour.  
H229: Pressurised container: May burst if heated  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H411: Toxic to aquatic life with long lasting effects.  
H412: Harmful to aquatic life with long lasting effects.  
R11: Highly flammable.  
R12: Extremely flammable.  
R36: Irritating to eyes.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65: Harmful: may cause lung damage if swallowed.  
R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.