

SAFETY DATA SHEET FUEL SYSTEM CLEANER DIESEL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FUEL SYSTEM CLEANER DIESEL

Product number QFD300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

Manufacturer TETROSYL LIMITED

Bury Lancashire England BL9 7NY 0161 764 5981 0161 797 5899 info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Acute Tox. 4 - H332 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram







Signal word

Danger

FUEL SYSTEM CLEANER DIESEL

Hazard statements H302+H332 Harmful if swallowed or if inhaled.

> H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Contains DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSINE - UNSPECIFIED, 2-

ETHYLHEXYL NITRATE, 2-ETHYLHEXAN-1-OL

Detergent labelling ≥ 30% aliphatic hydrocarbons

statements

Supplementary precautionary P301+P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT;

KEROSINE - UNSPECIFIED

CAS number: -EC number: 926-141-6 REACH registration number: 01-

2119484819-18-0001

60-100%

Classification

Asp. Tox. 1 - H304

2-ETHYLHEXYL NITRATE 10-<30%

CAS number: 27247-96-7 EC number: 248-363-6 REACH registration number: 01-

2119539586-27-0000

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Aquatic Chronic 2 - H411

FUEL SYSTEM CLEANER DIESEL

2-ETHYLHEXAN-1-OL 2.5-<5.0%

CAS number: 104-76-7 EC number: 203-234-3 REACH registration number: 01-

2119487289-20-0000

Classification

Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination. Keep the affected person warm and at

rest. Get prompt medical attention.

Inhalation Get medical attention if any discomfort continues. Move affected person to fresh air and keep

warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this

Safety Data Sheet to the medical personnel.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if a

large quantity has been ingested. Show this Safety Data Sheet to the medical personnel.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Rinse with

water. Get medical attention if irritation persists after washing.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention

promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Effects may be delayed. Keep affected person under observation.

Inhalation No specific symptoms known.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and

dermatitis. Blistering may occur.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor
No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-

extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

FUEL SYSTEM CLEANER DIESEL

Specific hazards Closed containers can burst violently when heated, due to excess pressure build-up. Risk of

explosion if heated.

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Leave danger zone immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and

surfaces. Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation.

Avoid inhalation of spray mist and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of

spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames

or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers

and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Good personal hygiene procedures should be implemented. Wash hands and any other

contaminated areas of the body with soap and water before leaving the work site. Avoid eating, drinking and smoking when using the product. Avoid contact with skin and eyes. Do

not handle broken packages without protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly-closed, original container. Keep away from heat,

sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

8.2. Exposure controls

FUEL SYSTEM CLEANER DIESEL

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any

occupational exposure limits for the product or ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves.

Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

Hygiene measures Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Wash

promptly with soap and water if skin becomes contaminated.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Dark. Brown.

Odour Strong. Characteristic.

pH Not determined.

Melting point Not determined.

Initial boiling point and range >190°C @

Flash point >62°C

Evaporation rate Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 0.837g/cm³ @ 20°C

Solubility(ies) Insoluble in water.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity 10 mm²/s @ 40°C

Explosive properties Not considered to be explosive.

FUEL SYSTEM CLEANER DIESEL

Explosive under the influence Not considered to be explosive.

of a flame

Oxidising properties

Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react strongly with the product: Alkaline earth metals. Powdered

metal.

10.2. Chemical stability

No particular stability concerns. Stability

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not applicable.

10.4. Conditions to avoid

Avoid heat. Avoid contact with the following materials: Strong oxidising agents. Avoid heat, Conditions to avoid

flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

ATE oral (mg/kg) 1,884.66

Acute toxicity - dermal

ATE dermal (mg/kg) 4,146.25

Acute toxicity - inhalation

ATE inhalation (gases ppm) 14,843.54

ATE inhalation (vapours mg/l) 36.28

ATE inhalation (dusts/mists

4.95

mg/l)

Inhalation Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis. Harmful by inhalation.

Ingestion Harmful if swallowed. Pneumonia may be the result if vomited material containing solvents

reaches the lungs.

FUEL SYSTEM CLEANER DIESEL

Skin contact Harmful in contact with skin. Repeated exposure may cause skin dryness or cracking.

Eye contact May cause temporary eye irritation.

chemical pneumonitis.

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic

invertebrates

Not available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface.

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and

local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (ADN) 3082

FUEL SYSTEM CLEANER DIESEL

14.2. UN proper shipping name

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2-

(ADR/RID) ETHYLHEXYL NITRATE)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2-

ETHYLHEXYL NITRATE)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2-

ETHYLHEXYL NITRATE)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 2-

ETHYLHEXYL NITRATE)

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID classification code M6

ADR/RID label 9

IMDG class 9

ICAO class/division 9

ADN class 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group

ADN packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

ADR transport category 3

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

FUEL SYSTEM CLEANER DIESEL

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Health & Safety Department

Revision date 07/02/2017

Revision 0

SDS number 32224

SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.